

Model	Flow (m ³ /h)	Head (m)	Speed (r/min)	Eff. (%)	NPSHr (m)
32-125	14.0	21.7	2900	55	1.0
32-160	14.5	34	2900	57	1.0
32-200	15.0	54	2900	47	1.4
32-250	20.0	86	2900	39	2.5
40-160	26.0	34.5	2900	63	1.2
40-200	27.5	54	2900	61	1.6
40-250	27.5	90	2900	52	1.4
40-315	30.5	132	2900	40	3.5
50-160	66	34	2900	75	2.2
50-200	72	49	2900	73	3.5
50-250	60	90	2900	69.5	3.0
50-315	58	135	2900	52	2.1
65-160	95	34	2900	79	2.8
65-200	100	53	2900	77	2.8
65-250	93	87	2900	69	2.5
65-315	98	129	2900	65	2.9
80-160	156	34	2900	82	4.9
80-200	155	52	2900	83	4.2
80-250	156	87	2900	77	3.8
80-315	160	128	2900	69	3.0
100-200	235	52	2900	85	5.0
100-250	255	84	2900	83	4.2
100-315	242	134	2900	76	4.2
32-125	7.5	5.2	1450	41	0.6
32-160	8.3	8.4	1450	50	0.8
32-200	7.5	13.4	1450	43	0.8
32-250	9.8	21	1450	38	0.9
40-160	12.5	8.4	1450	58	0.8
40-200	14.5	12.7	1450	56.5	1.0
40-250	14.6	21.5	1450	45	1.0
40-315	15	33	1450	37	0.7
50-160	34.5	8.2	1450	71.5	1.0
50-200	38	12	1450	72	1.0

Model	Flow (m ³ /h)	Head (m)	Speed (r/min)	Eff. (%)	NPSHr (m)
50-250	31	22	1450	63.5	1.0
50-315	30	32.7	1450	51	0.7
65-160	47	8.5	1450	74	0.5
65-200	52	13	1450	74	1.2
65-250	48	21.5	1450	64	1.2
65-315	47	32.5	1450	61.5	0.7
80-160	84	7.9	1450	77	1.5
80-200	87	13	1450	79	1.6
80-250	84	20.5	1450	76	1.4
80-350	77	32.5	1450	67	1.1
80-400	91	53	1450	65	2.4
100-200	115	12	1450	80	1.8
100-250	139	20.5	1450	81	1.7
100-315	130	32.5	1450	75	1.5
100-400	125	52	1450	70	1.2
125-250	215	20	1450	84	2.2
125-315	190	33.5	1450	82	1.7
125-400	215	51	1450	76.5	1.7
150-250	360	17	1450	82	2.7
150-315	370	31.8	1450	83	2.7
150-400	360	50.5	1450	77	2.9
150-500	360	82	1450	76	2.7
200-250	580	14.6	1450	85	4.8
200-315	610	28.5	1450	87	3.2
200-400	610	52	1450	84	3.9
200-500	575	82	1450	83	3.5
250-315	940	23.5	1450	84	4.6
250-400	940	46	1450	87	4.5
250-500	1075	74	1450	85	4.7
300-400	1420	41	1450	85	5.8
300-500	1580	70	1450	86	6.0

Model	Flow (m ³ /h)	Head (m)	Speed (r/min)	Eff. (%)	NPSHr (m)
25-160	9.4	29	2900	38.5	0.6
25-200	7.4	48	2900	28.5	1.4
40-160	12.5	34	2900	50	0.85
40-200	16	52	2900	47	1.1
40-250	29.5	75	2900	43	2.3
40-315	31	115	2900	36	2.2
50-160	59	32	2900	73	1.7
50-200	68	50	2900	72	3.3
50-250	60	76	2900	57.5	2.2
50-315	67	120	2900	52	3.2
50-400	77	160	2900	50	3.2/3.7
80-160	162	31	2900	81.5	5.3
80-200	163	50	2900	79	4.3
80-250	148	80	2900	73	2.8
80-315	160	125	2900	68.5	4.0
80-400	178	204	2900	62	3.9
100-200	240	45	2900	77	5.2
100-250	235	70	2900	77	4.0
100-315	265	130	2900	74	4.1
100-400	240	218	2900	68	4.75
150-250A	395	81	2900	80	7.1
150-250B	330	72	2900	78	5.0
150-315	380	129	2900	76	7.0
150-400	430	204	2900	72	6.7
200-250	625	66	2900	83	9.5
200-315	645	116	2900	82	9.4
200-400	660	201	2900	79	10.0
25-160	4.7	7	1450	35	0.4
25-200	3.8	12	1450	25	1.2
40-160	6.3	8.5	1450	46	0.5
40-200	8.2	13.1	1450	44	0.7
40-250	14.5	19	1450	39	1.3
40-315	15.5	29	1450	35	1.8
50-160	30	7.8	1450	67	0.5
50-200	33.5	12.5	1450	71	1.0

Model	(m ³ /h)	(m)	(r/min)	(%)	NPSHr (m)
50-250	30	19	1450	53	1.0
50-315	33	30	1450	51	1.0
50-400	38	40	1450	49	0.95
80-160	81	7.6	1450	77	1.9
80-200	80	12.5	1450	75	1.5
80-250	69	20.6	1450	70	1.5
80-315	80	31	1450	66	1.4
80-400	88	44	1450	51	1.2
100-200	120	11.4	1450	76	2.1
100-250	116	18	1450	76	1.5
100-315	134	32.5	1450	74	1.45
100-400	120	54	1450	68	1.4
150-250A	195	20.5	1450	79	2.1
150-250B	167	18	1450	76	1.5
150-315	195	32	1450	74	1.45
150-400	211	52	1450	68	1.4
200-250	320	16.3	1450	80	2.95
200-315	325	29	1450	82	2.9
200-400	360	49	1450	79	2.9

Model	Flow (m ³ /h)	Head (m)	Speed (r/min)	Eff. (%)	NPSHr (m)
40-250	29.5	75	2900	43	2.3
50-200	68	50	2900	72	3.3
50-400	77	160	2900	52	3.2
80-200	163	50	2900	79	4.3
80-250	148	80	2900	73	2.8
80-315	160	125	2900	68.5	4.0
100-200	240	45	2900	77	5.2
100-250	235	70	2900	77	4.0
100-315	265	130	2900	74	4.1
150-250A	395	81	2900	80	7.1
150-250B	330	72	2900	78	5.0
150-315	380	129	2900	76	7.0
200-315	645	116	2900	82	9.4
40-250	14.5	19	1450	39	1.3
50-200	33.5	12.5	1450	71	1.0
50-400	38	40	1450	49	0.95
80-200	80	12.5	1450	75	1.5
80-250	69	20.6	1450	70	1.5
80-315	80	31	1450	66	1.4
100-200	120	11.4	1450	76	2.1
100-250	116	18	1450	76	1.5
100-315	134	32.5	1450	74	1.45
150-250A	195	20.5	1450	79	2.2
150-250B	167	18	1450	77	1.6
150-315	195	32	1450	76	1.8
200-315	325	29	1450	82	2.9
200-401	575	54	1450	85	3.3
200-501	560	82	1450	82.5	3.4
250-401	960	45	1450	87	4.5
250-501	1100	74	1450	85	4.8