

Model	Capacity		Head m	Speed r/min	Efficiency %	NPSHr m	Shaft power km	Motor power km	Weight kg
	m ³ /h	L/s							
80NW-43×4	28.5	7.92	182	2950	56.5	2.0	25	37	287
	36	10	170		60	2.0	27.8		
	43	11.9	156		61	2.3	29.94		
100NW-56×4	40	11.1	250	2950	58	2.6	46.9	75	425
	53	14.7	220		61	2.6	50.9		
	63	17.5	187		62	3.0	54.8		
150NW-28×8	144	40	248	1450	76	2.0	128.9	185	1295
	180	50	230		78.8	2.7	144.5		
	210	58.3	208		77	3.7	149.9		
250NW-44×5	207	57.5	238	1450	75	1.8	178.9	315	2000
	270	75	231		79	2.5	214.9		
	315	87.5	222		78	3.5	244.1		
100NW-65×2	28	7.8	134	2930	49	1.6	21.3	30	300
	36	10	130		55	1.5	23.2		
	43	11.9	124		59	1.5	24.5		
125NW-65×2	43	11.9	133	2930	58.5	1.6	27	37	333
	57	15.8	130		65	1.5	31		
	67	18.6	125		67	1.5	34		
150NW-78×2	54	15	163	2970	58	1.9	41.3	55	430
	69	19.2	156		61	2.0	48.1		
	82.8	23	145		60.5	3.0	54		
150NW-90×2	104	28.9	190	2980	63.3	2.2	85	110	436
	134	37.2	180		68	2.0	96.5		
	161	44.7	166		68.8	2.5	105.7		
150NW-115×2	78	21.7	245	2980	56	2.2	92.9	132	531
	105	29.2	230		60	2.3	109.6		
	116	32.2	222		59.6	2.5	117.6		
200NW-65×2	150	41.7	139	2950	71.3	2.6	79.6	110	550
	182	50.6	130		74.5	2.5	86.5		
	205	56.9	122		72	2.6	94.6		