

Model	Capacity		Head	Speed	Efficiency	Shaft power	Motor Power	NPSHr	Nominal dia of impeller (mm)	Inlet and outlet Flange (mm)	
	L/S	m <sup>3</sup> /h	m	r/min	%	KW	KW	m		Inlet	Outlet
65-270A	23.1	83	195	2900	74	59.6	90	3.8	275	100	65
	28.6	103	183		75.5	68.0		5.5			
	34.4	124	158		72.5	73.6		17			
	21.7	78	167		73	48.6	3.3	255			
	26.9	97	154		74.5	54.6	5.7				
	32.2	116	138		72.5	60.1	15				
	19.4	70	141		70.5	38.1	3	235			
	24.4	88	128		73	42.0	4.1				
29.2	105	114	71.5	45.6	10						
65-270B	18.9	68	194	2900	73	49.2	75	4.8	275	100	65
	23.6	85	166		74	51.9		7.3			
	28.3	102	145		71.5	56.3		10			
	16.9	61	159		71.5	36.9	4	255			
	21.1	76	144		73	40.8	5.3				
	25.6	92	129		71.5	45.2	10				
	15.8	57	135		70.0	30.0	4	235			
	20.0	72	120		72.5	32.5	5				
23.9	86	106	71	35	7						
80-250A	31.9	115	163	2900	77.5	65.9	90	6	254	100	80
	40	144	150		79	74.5		8.2			
	48.1	173	135		77	82.6		9			
	30.3	109	138		76.5	53.5	6.4	236			
	38.1	137	126		79	59.5	7.3				
	45.6	164	110		77.5	63.4	9				
	28.9	104	117		74	44.8	6.5	219			
	36.1	130	104		76	48.4	7.5				
43.3	156	92	75	52.1	8.7						
80-250B	27.2	98	151	2900	77	52.3	75	5.8	254	100	80
	33.3	120	137		78.5	57.0		7			
	40.8	147	119		75.5	63.1		9			
	24.4	88	130		75	41.5	5.7	236			
	29.4	106	120		76	45.7	6.3				
	37.2	134	102		74	50.3	8.2				
	22.8	82	113		73	34.6	5.3	219			
	28.3	102	103		75	38.1	6				
34.2	123	89	72.5	41.1	7.5						

Model	Capacity		Head	Speed	Efficiency	Shaft power	Motor Power	NPSHr	Nominal dia of impeller (mm)	Inlet and outlet Flange (mm)	
	L/S	m <sup>3</sup> /h	m	r/min	%	KW	KW	m		Inlet	Outlet
80-310A	40.8	147	271	2900	76	142.7	200	6.4	325	125	80
	48.9	176	252		77	156.9		9.8			
	58.3	210	224		75	170.8		15			
	37.2	134	232		75.5	112.1	6	301			
	44.4	160	217		76.5	123.6	8.2				
	52.8	190	192		74	134.3	13				
	32.2	116	200		74	85.4	5		278		
	40.6	146	183		76.5	95.1	110				
48.6	175	160	73.5	103.7	12						
80-310B	30.6	110	261	2900	73	107.1	160	6.4	325	125	80
	38.3	138	241		75	120.8		8			
	45.8	165	214		73	131.7		12			
	28.3	102	224		72.5	85.8	6	310			
	35.6	128	206		74.5	96.4	132		7.8		
	43.1	155	183		73	105.8	11				
	27.8	100	184		73.5	68.2	6		278		
	33.3	120	173		74	76.4	90				
40.0	144	153	72.5	82.8	9.9						
100-290A	59.4	214	234	2900	79	172.6	250	6.6	301	150	100
	74.2	267	216		81	193.9		7.7			
	89.2	321	187		78.5	208.2		10.8			
	52.8	190	200		77.5	133.5	6.5	276			
	66.1	238	180		79	147.7	200		7.7		
	79.2	285	156		77	157.2	8.8				
	47.8	172	165		75	103.1	6.7		254		
	59.4	214	149		77	112.8	132				
71.1	256	130	76	119.3	8						
100-290B	53.1	191	226	2900	78	150.7	200	7.2	301	150	100
	66.1	238	202		80	163.7		7.8			
	79.7	287	172		77.5	173.5		10.3			
	48.3	174	187		76.5	115.8	6.6	276			
	58.3	210	172		79	124.5	160		7.3		
	70.0	252	147		77.5	130.2	8.9				
	42.8	154	156		74.5	87.8	6.6		254		
	51.4	185	144		76	95.5	110				
61.7	222	125	75	100.8	7.8						

Model	Capacity		Head	Speed	Efficiency	Shaft power	Motor Power	NPSHr	Nominal dia of impeller (mm)	Inlet and outlet Flange (mm)			
	L/S	m <sup>3</sup> /h	m	r/min	%	KW	KW	m		Inlet	Outlet		
150-520A	90.8	327	194	1450	79	218.7	315	2.7	530	200	150		
	113.8	408	182		81	249.7		3.2					
	136.1	490	166		78.5	282.2		5					
	83.9	302	165		77.5	175.1	2.7	250	486				
	105.0	378	153		79.5	198.1	2.9						
	125.8	453	140		78	221.4	6.2						
	78.3	282	134		75	137.2	2.7					200	442
	98.1	353	125		78	154.1	3.7						
117.5	423	110	75.5	167.8	7.5								
150-520B	81.7	294	176	1450	78	180.7	250	2.2	530	200	150		
	101.9	367	163		80	203.6		3					
	122.2	440	146		78.5	222.9		4.4					
	77.2	278	150		76.5	148.4	2.1	200	486				
	96.4	347	136		78.5	163.7	3.1						
	115.8	417	120		76.5	178.1	4.6						
	70.0	252	122		75	111.6	2					160	442
	87.5	315	112		77	124.8	2.6						
105.0	378	101	75.5	137.7	4.5								
150-670A	88.1	317	316	1450	74.5	366.2	500	2.6	655	200	150		
	110.0	396	300		78	414.8		3.1					
	130.0	468	280		74	482.2		4.6					
	79.2	285	272		73.5	287.2	2.5	400	611				
	98.1	353	256		77	319.6	2.7						
	117.8	424	236		73	373.3	3.7						
	71.7	258	229		73	220.4	2.5					315	568
	90.0	324	220		74	262.3	3						
108.3	390	200	72	295	3.3								
150-670B	77.8	280	286	1450	75	290.8	400	2.3	655	200	150		
	97.2	350	268		77	331.7		2.9					
	116.7	420	245		73	383.9		4.3					
	69.4	250	248		74	228.2	2.2	315	611				
	87.5	315	233		76	263.0	2.6						
	102.8	370	216		73	298.1	3.3						
	65.3	235	214		72	190.2	2.2					280	568
	82.5	297	201		75	216.8	2.5						
100.0	360	180	73	241.7	3.4								

Model	Capacity		Head m	Speed r/min	Efficiency %	Shaft power KW	Motor Power KW	NPSHr m	Nominal dia of impeller (mm)	Inlet and outlet Flange (mm)	
	L/S	m <sup>3</sup> /h								Inlet	Outlet
200-600A	138.1	497	252	1450	80	426.3	630	3	610	250	200
	172.5	621	236		81	492.7		4.2			
	206.9	745	210		79	539.3		6			
	129.4	466	216		79.5	344.8	3	568			
	161.9	583	200		80.5	394.5	4.5				
	194.4	700	177		78.5	429.8	7.1	520			
	122.2	440	181		78	278.1	3				
	150.0	540	166		80	305.1	3.5				
180.6	650	147	77.5	335.8	6						
200-600B	122.2	440	222	1450	78	341.0	450	3	610	250	200
	152.8	550	202		80	378.2		3.9			
	183.3	660	176		79	400.4		5.7			
	111.1	400	193		77.5	271.3	2.9	568			
	138.9	500	176		79.5	301.4	3.4				
	166.7	600	157		78	328.9	5.6	520			
	100.0	360	162		77	206.3	2.8				
	126.1	454	150		79	234.8	3.3				
150.0	540	130	77	248.3	4.7						
250-510A	290.0	1044	157	1450	82.5	541.4	710	6.1	518	350	250
	362.5	1305	142		84.5	597.2		6.7			
	435.0	1566	120		81.5	627.9		8			
	270.0	972	135		81	441.2	6.8	482			
	337.5	1215	120		83.5	475.5	7.3				
	405.0	1458	100		81	490.2	8.6	445			
	248.1	893	115		78	358.6	7.5				
	310.0	1116	100		81.5	372.9	7.7				
371.9	1339	80	78	374.0	8.9						
250-510B	271.9	979	151	1450	83	485.0	630	6.2	518	350	250
	340.0	1224	135		84.5	532.5		7			
	408.1	1469	113		83	544.7		8.4			
	251.9	907	134		81.5	406.1	6.7	482			
	315.0	1134	119		84	437.5	7				
	378.1	1361	100		81.5	457.8	8.2	445			
	227.8	820	116		78	332.1	7				
	285.0	1026	100		83	336.6	7.4				
341.9	1231	85	80.5	354.0	8.2						

If you want to get more detailed information, please contact us!