SELECTING THE RIGHT BRUSH

Need to clean a surface without removing base material? Nothing beats a power-driven wire brush for cleaning hot welds. The high quality wheels, end and cup brushes from hovin can effectively handle tube end, corrosion, scale removal, inter-pass weld cleaning, and many other jobs. The varied trim lengths, knot configurations and wire sizes in our lineup offer optimal speed and effectiveness for any job.

BRUSH TYPES | CONFIGURATIONS



Standard Twist Provides some flexibility for use on irregular surfaces. Sharp wire tips make this knot aggressive right from the start.



Hurricane Twist Provides smoother operation but sacrifices much of the cleaning action.



Cable Twist Provides very aggressive brushing action. Sharp wire tips make this knot aggressive right from the start.



Stringer Bead Twist High-impact action, primarily for weld cleaning. Sharp wire tips make this knot aggressive right from the start.



Wheel Brushes

For root and hot pass weld cleaning, heavy deburring, deflashing, surface prep, remove oxides and rust.



Bevel Brushes

For aggressive-yet-flexible brushing action for cleaning fillet welds and into corners.



Cup Brushes

For weld prep on large surface areas, heavy deburring, surface prep, remove oxides and rust.



End Brushes

For weld cleaning applications in recessed areas, heavy deburring, surface prep, remove oxides and rust.





Crimped



Twist Knotted





Nylon

SUPERIOR MATERIALS:

uses wire that is harder, stronger, and more resistant to fatigue. We utilize high tensile steel wire that is heat-treated to the most exacting standards for superior fatigue resistance and aggressive brushing. Every lot of wire is inspected and tested to ensure consistency and quality

SUPERIOR CONSTRUCTION:

Sharp wire tips mean faster cleaning action. Trimmed wire ends ensure the wire tips are sharp and ready to work right out of the box. Also the greater knot twist delivers a more aggressive brush and increases brush life.

Stringer Bead Knotted Wheels



STRINGER BEAD WHEELS

HOYIN's wheels offer professional grade quality and performance at a great value. Re-engineered, these 32/36 knot wheels deliver 20% MORE life while maintaining aggressive cleaning power for weld cleaning applications.

The 4" 4-1/2" wheels are manufactured using similar product construction and to the same exacting standards as other HOYIN weld cleaning brushes; they have been engineered for cost-effective use in less demanding cleaning applications.

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item Number		
Diamotor	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless	
4" (100mm)	.020" (0.5mm)	5/8"-11NC M14X 2	32	1/4" (6mm)	7/8" (22mm)	20,000	10	29136	29139	
4 1/2" (115mm)	.020" (0.5mm)	5/8"-11NC M14X2	36	1/4" (6mm)	13/16" (21mm)	15,000	10	29137	29140	





HOYIN STRINGER BEAD WHEELS are manufactured using similar product construction and to the same exacting standards as other HOYIN weld cleaning rushes; they have been engineered for cost effective use in less demanding applications.

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item	Number
Diameter	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless
5" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	38	3/16"	7/8" (22mm)	12,500	10	29142	29148
6" (150mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	48 38	1/4" 3/16"	1-1/4"(32mm) 1-3/8"(38mm)	12,500	10	29143	29149
7" (175mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	52	3/16"	1-3/8" (38mm)	9,000	10	29145	29151
8" (200mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	56	3/16"	1-3/5" (40mm)	9,000	10	29146	29152



Standard Knotted Wheels



STRINGER BEAD WHEELS EN1083-2 Standard

FEATURES AND BENEFITS

Provides flexible brushing action and cost effective performance in general purpose cleaning applications

Suitable for right angle grinder tool usage

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item N	Item Number		
Diameter	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless		
4" (100mm)	.020" (0.5mm)	5/8"-11NC M14X 2	20	1/4" (6mm)	7/8" (22mm)	20,000	10	29154	29158		
4 1/2" (115mm)	.020" (0.5mm)	5/8"-11NC M14X2	20	1/4" (6mm)	13/16" (21mm)	12,500	10	29155	29159		



P STRINGER BEAD WHEELS EN1083-2 Standard

FEATURES AND BENEFITS

Feature a hex nut design that simlifies periodic flipping of the wheel for maximum cleaning action,long life, and safer use.

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item	Number
Didiliotoi	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless
5" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	24	1/2"	1" (24mm)	12,500	10	29161	29167
6" (150mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	24 30	1/2"	1" (26mm)	12,500	10	29162	29168
7" (175mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	30	31/2"	1-3/8" (38mm)	9,000	10	29164	29170
8" (200mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	35	1/2"	1-3/5" (40mm)	9,000	10	29165	29171

Crimped Wire Wheels



Crimped Wire Wheel.Narrow Face

FEATURES AND BENEFITS

Intended for use on straight grinders and stationary machines such as bench or pedestal grinders and buffing lathes

Provides a flexible brushing action and consistent performance for demanding light duty cleaning and deburring applications

1/2 in T of face plates

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
4"	0000110 0	5/8"-1/2"	Steel	4.007.40				29173
(100mm)	.006"(0.2mm) .012"(0.3mm)	5/8"-11NC	Coated Brass	1/2"(13mm) 5/8"(16mm)	22mm	6,000	10	29174
(,	(**************************************	M14X2	Stain l ess					29176
6"	.006"(0.2mm)	5/8"-1/2"	Steel					29177
(150mm)	.006 (0.2mm)	5/8″-11NC	Coated Brass	1/2"(13mm) 5/8"(16mm)	22mm	4,500	10	29179
(10011111)		M14X2	Stainless	0,0 (1011111)				29180
8"	.006"(0.2mm)	5/8"-1/2"	Steel					29182
(200mm)	.012"(0.3mm)	5/8"-11NC	Coated Brass	1/2"(13mm) 5/8"(16mm)	40mm	4,500	6	29183
(20011111)		M14X2	Stainless	3.3 (.011111)				29185



P Crimped Wire Wheel, Narrow Face

FEATURES AND BENEFITS

Feature a shorter trim length, narrower face width and the same durable construction as other crimped wire wheels

Designed specifically for use on small bench grinders for reduced flaring and long life in a broad range of applications

Tool: bench grinder and pedestal grinder

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
6" (150mm)	.012"(0.3mm) .014"(0.35mm)	5/8"-1/2"	Steel Coated Brass	3/4"(19mm) 1"(25mm)	30mm	6,000	6	29186 29188
8"	.012"(0.3mm)		Steel	3/4"(19mm)	40	4.500		29189
(200mm)	.014"(0.35mm)	5/8"-1/2"	Coated Brass	1"(25mm)	40mm	4,500	6	29191





Stringer Bead Knotted Wheels



STRINGER BEAD WHEELS

Narrow face brushes are suitable for cleaning root and hot passes and reaching into corners

Engineered for cost-effective use in less demanding applications

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	item i	Number
Diameter	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless
4" (100mm)	.020" (0.5mm)	5/8"-11NC M14X 2	32	1/4" (6mm)	7/8" (22mm)	12,500	10	29192	29194
4 1/2" (115mm)	.020" (0.5mm)	5/8"-11NC M14X2	36	1/4" (6mm)	13/16" (21mm)	10,000	10	29195	29197



STRINGER BEAD WHEELS


Narrow face brushes are suitable for cleaning root and hot passes and reaching into corners

Engineered for cost-effective use in less demanding applications

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item	Number
Diamotor	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless
5" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	38	3/16"	7/8" (22mm)	10,000	10	29198	29204
6" (150mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	48 38	1/4" 3/16"	1-1/4"(32mm) 1-3/8"(38mm)	9,000	10	29200	29206
7" (175mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	52	3/16"	1-3/8" (38mm)	9,000	10	29201	29207
8" (200mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	56	3/16"	1-3/5" (40mm)	9,000	10	29203	29209



Standard Knotted Wheels



Knotted Wire Wheel Brushes FEATURES AND BENEFITS

Provide an aggressive brushing action for general purpose deburring cleaning and surface preparation applications

Knot wire wheels with an arbor hole are intended for use on straight grinders and stationary machines such as bench or pedestal grinders and buffing lathes

Featuring Weiler's individual knot hole construction, these radial brushes are available in heat-treated steel, type 302 stainless steel and bronze wire for use in a wide variety of applications

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item N	Item Number		
Diamotor	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless		
4" (100mm)	.020" (0.5mm)	5/8"-11NC M14X 2	20	1/4" (6mm)	7/8" (22mm)	12,500	10	29210	29123		
4 1/2" (115mm)	.020" (0.5mm)	5/8"-11NC M14X2	20	1/4" (6mm)	13/16" (21mm)	12,500	10	29212	29125		



Knotted Wire Wheel Brushes

FEATURES AND BENEFITS

Provide an aggressive brushing action for general purpose deburring cleaning and surface preparation applications

Knot wire wheels with an arbor hole are intended for use on straight grinders and stationary machines such as bench or pedestal grinders and buffing lathes

Featuring Weiler's individual knot hole construction, these radial brushes are available in heat-treated steel, type 302 stainless steel and bronze wire for use in a wide variety of applications

Diameter	Wire	Arbor	No. of	Face	Trim	Max.	Standard	Item N	lumber
Diameter	Size	Hole	Knots	Width	Length	RPM	Pack	Steel	Stainless
5" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	24	1/2"	1" (25mm)	10,000	10	29127	29222
6" (150mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	24 30	1/2"	1" (25mm)	9,000	10	29127	29223
7" (175mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	30	31/2"	1-3/8" (38mm)	9,000	10	29219	29225
8" (200mm)	.020" (0.5mm)	5/8"-11NC M14X 2 7/8"(22mm)	35	1/2"	1-3/5" (40mm)	9,000	10	29220	29226

Crimped Wire Wheels





Crimped Wire Wheel, Narrow Face FEATURES AND BENEFITS

Provides a flexible brushing action and consistent performance for demanding light duty cleaning and deburring applications Feature a wider face width to cover more area Covers more surface area in a single pass

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
4" (100mm)	.006"(0.2mm) .012"(0.3mm) .014"(0.35mm)	M14X2 5/8"-11NC 5/8"(16mm)	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	22mm	4,500	10	29228
4-1/2" (115mm)	.006"(0.2mm) .012"(0.3mm) .014"(0.35mm)	M14X2 5/8"-11NC 5/8"(16mm)	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	23mm	4,500	10	84170
5" (125mm)	.006"(0.2mm) .012"(0.3mm) .014"(0.35mm)	M14X2 5/8"-11NC 5/8"(16mm)	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	29mm	4,500	10	84173
6" (150mm)	.006"(0.2mm) .012"(0.3mm) .014"(0.35mm)	M14X2 5/8"-11NC 5/8"(16mm)	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	33mm	4,500	10	84176
7" (175mm)	.006"(0.2mm) .012"(0.3mm) .014"(0.35mm)	M14X2 5/8"-11NC 5/8"(16mm)	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	33mm	4,500	10	84179
8" (200mm)	.006"(0.2mm) .012"(0.3mm) .014"(0.35mm)	M14X2 5/8"-11NC 5/8"(16mm)	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	41mm	4,500	10	84182



Crimped Wire Wheel, Wide Face

FEATURES AND BENEFITS

Provides a flexible brushing action and consistent performance for demanding light duty cleaning and deburring applications
Feature a wider face width to cover more area

Covers more surface area in a single pass

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
6"	.012"(0.3mm)		Steel	3/4"(19mm) 1"(25mm)	30mm	6,000	6	84185
(150mm)	.014"(0.35mm)		Coated Brass	1 (23/11/11)				84188
8"	.012"(0.3mm)	E/0" 4/0"	Steel	3/4"(19mm)	100000	4 500	6	84191
(200mm)	.014"(0.35mm)	5/8"-1/2"	Coated Brass	1"(25mm)	40mm	4,500		84195

Bevel Wire Brushes



Knooted Bevel Wire Wheel Brushes

FEATURES AND BENEFITS

STANDARD TWIST BEVEL BRUSHES feature a tufted knot end and a saucer shaped radial wheel to provide an aggressive-yet-flexible brushing action for cleaning fillet welds and into corners.

Diameter	Wire Size	Arbor [.] Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
4" (100mm)	.014"(0.35mm) .020"(0.5mm)	M14X2 5/8"-11NC	Steel	1/2"	3/4"(19mm)	12,500	10	84226
4-1/2" (115mm)	.014"(0.35mm) .020"(0.5mm)	M14X2 5/8"-11NC	Steel	1/2"	3/4"(19mm)	12,500	10	84229
5" (125mm)	.020"(0.5mm)	M14X2 5/8"-11NC	Steel	1/2"	1"(25mm)	12,500	10	84232



Crimped Bevel Wire Wheel Brushes FEATURES AND BENEFITS

Provides a flexible brushing action and consistent performance for demanding light duty cleaning and deburring applications

Feature a wider face width to cover more area Covers more surface area in a single pass

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
4"	.014"(0.35mm)	M14X2	Steel		7/8"(22mm)	40.500	40	84235 84238
(100mm)	.012"(0.3mm)	5/8"-11NC	Stainless Coated Brass		170 (2211111)	12,500	10	84241
4-1/2"	.014"(0.35mm)	M14X2	Steel				40	84244
(115mm)	.012"(0.3mm)	5/8"-11NC	Stainless		1"(25mm)	12,500	10	84248
E"	.014"(0.35mm)		Coated Brass Steel					84251 84254
(105,000)	' '	WHAZ	Stainless		1-1/8"(30mm)	12,500	10	84257
(125mm)	.012"(0.3mm)	5/8"-11NC	Coated Brass		(**************************************			84260



Crimped Wire Wheels





Crimped Wire Wheel, Wide Face **FEATURES AND BENEFITS**

Provides a flexible brushing action and consistent performance for demanding light duty cleaning and deburring applications Feature a wider face width to cover more area Covers more surface area in a single pass

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
4" (100mm)	.012"(0.3mm) .014"(0.35mm)	32mm Adapter:1/2" 5/8" 3/4" 7/8" 1"	Steel Stainless Brass Coated	3/ 4 "(19mm)	21mm	6,000	60	84198
5" (125mm)	.012"(0.3mm) .014"(0.35mm)	32mm Adapter:1/2" 5/8" 3/4" 7/8" 1"	Steel Stainless Brass Coated	3/4"(19mm) 1"(25mm)	30mm	6,000	60	84201
6" (150mm)	.012"(0.3mm) .014"(0.35mm)	32mm Adapter:1/2" 5/8" 3/4" 7/8" 1"	Steel Stainless Brass Coated	3/4"(19mm) 1"(25mm)	30mm	6,000	40	84204
7" (175mm)	.012"(0.3mm) .014"(0.35mm)	Lananier III aik l	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	40mm	6,000	20	84207
8" (200mm)	.012"(0.3mm) .014"(0.35mm)	ו אולי לוויים מחבים וו	Steel Stainless Brass Coated	1/2"(13mm) 5/8"(16mm)	40mm	4,500	20	84210

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
10" (250mm)	.012"(0.3mm) .014"(0.35mm)	HAUADIEL I/Z 5/0	Steel Coated Brass	3/4"(19mm) 1"(25mm)	50mm	4,500	10	84213 84217
12"	010"(0.2mm)	32mm Adanter:1/2" 5/8"	Steel Coated Brass	3/4"(19mm) 1"(25mm)	72mm	4,500	10	84220 84223

Diameter	Wire Size	Arbor Hole	Material	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number
6"	.012"(0.3mm)	50mm	Steel	1"(25mm) 1-1/4"(32mm)	50mm	4,500	10	84313
(150mm)	.014"(0.35mm)		Coated Brass	1=1/4 (3211 11)		4,500	.,	84317
8"	.012"(0.3mm)		Steel	1"(25mm)	70	4.500	10	84320
(200mm)	.014"(0.35mm)	50mm	Coated Brass	1-1/4"(32mm)	72mm	4,500	10	84323







HOYIN's wire cup brushes are intended primarily for use on portable power tools for addressing larger surface areas more efficiently than a wheel brush. Cup brushes are designed for smooth, efficient operation on angle grinders to make quick work of large jobs.

Cup brushes are available in a variety of knot wire and crimped wire configurations for use in a broad range of surface cleaning applications, and they are manufactured with individual knot hole and solid ring construction for high performance and long life. Weiler's cup brushes are available in heat-treated Steel, Type 304 Stainless Steel, and Brass wire



APPLICATIONS

- Removal of slag from the edges of plasma-cut or flame-cut plates
- Removing paint and coatings
- Cleaning rust, scale, and corrosion
- Deburring
- Weld prep and cleaning

CUP BRUSH SIZE SELECTION GUIDE

Brush Sizes	Angle Grinder Size
2-3/4" & 3"	4"
2-3/4", 3" & 3-1/2"	4-1/2"
2-3/4", 3" & 3-1/2"	5"
3-1/2" & 4"	6"
4", 5" & 6"	7"
4", 5" & 6"	9"

KNOT WIRE CUP BRUSHES Single Row

Provide heavy-duty brushing action with some flexibility; ideal for demanding cleaning applications on relatively flat surfaces.



Diameter	Wire	Arbor	Trim	Max.	Standard		ltem Number	1
Diameter	Size	Hole	Length	RPM	Pack	Steel	Stainless	Bronze
2 3/4" (75mm)	.014" (0.35mm)	5/8"-11NC M14X 2 M10X1.25 M10X1.5	1" (25mm)	12,500 14,000	1	84263	84295	84326
2 3/4" (75mm)	.020" (0.5mm)	5/8"-11NC M14X 2 M10X1.25 M10X1.5	1" (25mm)	12,500 14,000	1	84266	84298	84329
3-1/2" (90mm)	.014" (0.35mm)	5/8"-11NC M14X 2	1 1/8" (28mm)	12,500	1	84269	84302	84332
3-1/2" (90mm)	.020" (0.5mm)	5/8"-11NC M14X 2	1 1/8" (28mm)	12,500	1	84272	84305	84335
4" (100mm)	.014" (0.35mm)	5/8"-11NC M14X 2	1-1/4" (32mm)	8,500	1	84277	84308	84338
4" (100mm)	.020" (0.5mm)	5/8"-11NC M14X 2	1-1/4" (32mm)	8,500	1	84280	84311	84341
5" (125mm)	.014" (0.35mm)	5/8"-11NC M14X 2	1-3/8" (35mm)	6,500	1	84283	84314	84344
5" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2	1-3/8" (35mm)	6,500	1	84286	84317	84348
6" (125mm)	.014" (0.35mm)	5/8"-11NC M14X 2	1-3/8" (35mm)	6,000	1	84289	84320	84351
6" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2	1-3/8" (35mm)	6,000	1	84292	84323	84354







HOYIN's wire cup brushes are intended primarily for use on portable power tools for addressing larger surface areas more efficiently than a wheel brush. Cup brushes are designed for smooth, efficient operation on angle grinders to make quick work of large jobs.

Cup brushes are available in a variety of knot wire and crimped wire configurations for use in a broad range of surface cleaning applications, and they are manufactured with individual knot hole and solid ring construction for high performance and long life. Weiler's cup brushes are available in heat-treated Steel, Type 304 Stainless Steel, and Brass wire



APPLICATIONS

- Removal of slag from the edges of plasma-cut or flame-cut plates
- Removing paint and coatings
- Cleaning rust, scale, and corrosion
- Deburring
- Weld prep and cleaning

CUP BRUSH SIZE SELECTION GUIDE

Brush Sizes	Angle Grinder Size
2-3/4" & 3"	4"
2-3/4", 3" & 3-1/2"	4-1/2"
2-3/4", 3" & 3-1/2"	5"
3-1/2" & 4"	6"
4", 5" & 6"	7"
4", 5" & 6"	9"

P CRIMPED WIRE CUP BRUSHES

Provide very flexible brushing action and the most consistent performance for demanding light-duty cleaning applications; feature a threaded nut for use on angle grinders.



Diameter	Wire	Arbor	Trim Max.		Standard		ltem Number	
Diameter	Size	Hole	Length	RPM	Pack	Steel	Stainless	Bronze
3" (75mm)	.014" (0.35mm) .012" (0.3mm)	5/8"-11NC M14X 2 M10X1.25 M10X1.5	7/8" (23mm)	12,500 14,000	1	84357	84379	84401
3" (75mm)	.006" (0.2mm)	5/8"-11NC M14X 2 M10X1.25 M10X1.5	7/8" (23mm)	12,500 14,000	1	84360	84382	84404
3-1/2" (90mm)	.012" (0.3mm)	5/8"-11NC M14X 2	1" (25mm)	12,500	1	84364	84385	84407
4" (100mm)	.014" (0.35mm) .012" (0.35m)	5/8"-11NC M14X 2	1 1/8" (28mm)	8,500	1	84367	84388	84410
4" (100mm)	.006" (0.2mm)	5/8"-11NC M14X 2	1 1/8" (28mm)	8,500	1	84370	84391	84413
5" (125mm)	.014" (0.35mm) .012" (0.35m)	5/8"-11NC M14X 2	1-1/4" (32mm)	6,500	1	84373	84395	84416
6" (125mm)	.014" (0.35mm) .012" (0.35m)	5/8"-11NC M14X 2	1-1/4" (32mm)	6,000	1	84376	84398	84419







KNOT WIRE CUP BRUSHES Single Row

Provide flexible brushing action and cost-effective performance in general purpose cleaning applications





Diameter	Wire	Arbor	Trim	Max.	Standard		Item Numb	er
Diameter	Size	Hole	Length	RPM	Pack	Steel	Stainless	Bronze
3"	.014" (0.35mm)	5/8" - 11NC M14X 2	1"	12,500		84422	84442	84461
(75mm)	.020" (0.5mm)	M10X1.25 M10X1.5	(25mm)	12,500 1 14,000		84426	84445	84464
4"	.014" (0.35mm)	5/8"-11NC	1-1/4" (32mm)	0.500	1	84430	84448	84467
(100mm)	.020" (0.5mm)	M14X 2		8,500		84433	84451	84470
5"	.014" (0.35mm)	5/8" - 11NC		6,500	1	84436	84454	84473
(125mm)	.020" (0.5mm)	M14X 2	(35mm)	3,000	'	84439	84458	84476



Diameter	Wire	Arbor	Trim	Max.	Standard		Item Numbe	r
Diameter	Size	Hole	Length	RPM	Pack	Steel	Stainless	Bronze
2 1/2"	.020"	5/8"-11NC M14X 2	1"	12,500	1	84479	72369	72381
(65mm)	(0.5mm) M10X1.2	M10X1.25 M10X1.5	(25mm)	12,500		72359	72371	72383
3"	.014" (0.35mm)		1"	12 500	1	72360	72372	72384
(75mm)	.020" (0.5mm)	M10X1.25 M10X1.5	(25mm)	12,500		72362	72374	72386
4"	.014" (0.35mm)	5/8"-11NC	1-1/4" (32mm)	8,500	1	72363	72375	72387
(100mm)	.020" (0.5mm)	M14X 2			'	72365	72377	72389
5" (125mm)	.014" (0.35mm) .020" (0.5mm)	5/8"-11NC M14X 2	1 - 3/8" (35mm)	6,500	1	72366	72378	72390
6" (150mm)	.014" (0.35mm) .020" (0.5mm)	5/8"-11NC M14X 2	1-3/8" (35mm)	6,500	1	72368	72380	72392



Diameter	Wire	Arbor	Trim	Max.	Standard		Item Numbe	er
Diamotoi	Size	Hole	Length	RPM	Pack	Steel	Stainless	Bronze
2 1/2"	.020"	5/8" - 11NC M14X 2	5/8"	40.500	1	72393	72404	72414
(65mm)	(0.5mm)	M10X1.25 M10X1.5	(15mm)	12,500		72395	72405	72416
3"	.020"	5/8" - 11NC M14X 2	7/8"	8,500	1	72396	72407	72417
(75mm)	(0.5mm)	M10X1.25 M10X1.5	(23mm)	0,500		72398	72408	72419
4"	.020"	5/8"-11NC	1"	8,500	1	72399	72410	72420
(100mm)	(0.5mm)	M14X 2	(24mm)	0,000		72401	72411	72422
5" (125mm)	.020" (0.5mm)	5/8"-11NC M14X 2	7/8" (22mm)	6,500	1	72402	72413	72423



V Crimped WIRE CUP BRUSHES

Provide flexible brushing action and cost-effective performance in general purpose cleaning applications





Diameter	Wire	Arbor	Trim	Max.	Standard	item Number		
Diameter	Size	Hole	Length	RPM	Pack	Steel	Stainless	Coated Brass
3"	.006" (0.2mm)	5/8"-11NC M14X 2	1"	12,500	1	72425	72432	72440
(75mm)	.014" ´ (0.35mm)	M10X1.25 M10X1.5	(25mm)	14,000	·	72426	72434	72441
4"	.006" (0.2mm)	5/8" - 11NC	1-1/4"	8,500	1	72428	72435	72443
(100mm)	, ,	(32mm)	0,300		72429	72437	72444	
5" (125mm)	.014" (0.35mm)	5/8" - 11NC M14X 2	1-3/8" (35mm)	6,500	1	72431	72438	72446

▼ Crimped WIRE CUP BRUSHES





Diameter	Wire	Arbor	Trim	Max.	Standard	Item Number			
Didiliotoi	Size	Hole	Length	RPM	Pack	Steel	Stainless	Coated Brass	
2 1/2"	.006" (0.2mm)	5/8"-11NC M14X 2	1"	12,500	1	72447	72465	72483	
(65mm)	.012" (0.35mm)	M10X1.25 M10X1.5	(25mm)	12,500	_ '	72449	72467	72485	
0"		5/8"-11NC				72450	72468	72486	
3" (75mm)	.012" (0.35mm)	.012" M14X 2 0.35mm) M10X1.25 .014" M10X1.5	1" (25mm)	12,500	1	72452	72470	72488	
	.014" (0.35mm)					72453	72471	72489	
	.006" (0.2mm)			8,500	1	72455	72473	72491	
4" (100mm)	.012" (0.35mm)	5/8"-11NC M14X 2	1 - 1/4" (32mm)			72456	72474	72492	
	.014" (0.35mm)					72458	72476	72494	
5"	.012" (0.35mm)	5/8"-11NC	1-3/8"	6,500		72459	72477	72495	
(125mm)	.014" (0.35mm)	M14X 2	(35mm)	0,000	1	72461	72479	72497	
6"	.012" (0.35mm) _{5/8"-11NC} 1-3/8"		0.500	1	72462	72480	72498		
(150mm)	.014" (0.35mm)	M14X 2	(35mm)	6,500	1	72464	72482	72500	

THREADED ADAPTERS

For mounting brushes with a 5/8"-11 UNC/M14X2 nut to other threaded spindles.



Fixed Thread Size	Adapted Thread Size	Standard Pack	Item Number
5/8" - 11 UNC	M10 x 1.25	10	72501
5/8" - 11 UNC	M10 x 1.5	10	72503
M14X2	M10 x 1.25	10	72504
M14X2	M10 x 1.5	10	72506

STEM-MOUNTED END BRUSHES




HOYIN's wire end brushes are intended primarily for use on high-speed portable power tools for addressing smaller surfaces and recessed areas. End brushes feature an integral 1/4" Steel stem for safe operation at high speed and quick mounting into the collet or chuck of either electric or pneumatic die grinders. End brushes are manufactured with the highest quality construction for smooth, efficient performance and long life. HOYIN's end brushes are available in heat-treated Steel, Type 304 Stainless Steel, and Bronze wire.

APPLICATIONS

- Cleaning ID's, internal passages & recessed areas
- Removing die flash and excess molded material
- Deburring internal edges and cross-hole intersections
- Spot facing

P KNOT WIRE END BRUSHES





Diameter	Wire	Shank	Trim	Max.	Standard	Item	Number
Diameter	Size	Size	Length	RPM	Pack	Steel	Stainless
1/2" (12mm)	.014" (0.35mm) .02" (0.5mm)	1/4" 6mm	7/8" (23mm)	20,000	10	72507	72516
5/8" (15mm)	.014" (0.35mm) .02" (0.5mm)	1/4" 6mm	7/8" (23mm)	20,000	10	72509	72518
3/4" (19mm)	.014" (0.35mm) .02" (0.5mm)	1/4" 6mm	1 1/8" (28mm)	20,000	10	72510	72519
7/8" (22mm)	.014" (0.35mm) .02" (0.5mm)	1/4" 6mm	1 1/8" (28mm)	20,000	10	72512	72521
1" (25mm)	.014" (0.35mm) .02" (0.5mm)	1/4" 6mm	1-1/4" (32mm)	20,000	10	72513	72522
1 1/8" (30mm)	.014" (0.35mm) .02" (0.5mm)	1/4" 6mm	1-1/4" (32mm)	20,000	10	72515	72524

KNOT WIRE END BRUSHES





Diameter	Wire	Shank	Trim	Max.	Standard	Item Number		
Diamotor	Size	Size	Length	RPM	Pack	Steel	Stainless	
1"	.014" (0.35mm)	1/4"	7/8"	20,000	10	70505	70500	
(25mm)	.02" (0.5mm)	6mm	(23mm)	20,000	10	72525	72528	
1-1/8"	.014" (0.35mm)	1/4"	7/8"	20,000	10	72527	72530	
(28mm)	.02" (0.5mm)	6mm	(23mm)	20,000	10	. 2321	. 2000	

STEM-MOUNTED END BRUSHES

KNOT WIRE END BRUSHES





Diameter	Wire	Shank	Trim	Max. RPM	Standard Pack	Item Number		
Diallictei	Size	Size	Length			Steel	Stainless	
1"	.014" (0.35mm)	1/4"	1-1/8"	4,500	10	72531	72537	
(25mm)	.02" (0.5mm)	6mm	(28mm)			72533	72539	
1-1/8"	.014" (0.35mm)	1/4"	1-1/8" (28mm)	4,500	10	72534	72540	
(28mm)	`.02" ′ (0.5mm)	6mm				72536	72542	


CRIMPED WIRE END BRUSHES



Features a solid end construction and very flexible brushing, ideal for more demanding light-duty cleaning applications in corners and hard-to-reach areas.

Diameter	Wire	Shank	Trim	Max.	Standard	item i	Number
Diallicter	Size	Size	Length	RPM	Pack	Steel	Stainless
1/2"	.006" (0.2mm)	1/4"	7/8"		40	72543	72552
(12mm)	`.012" [′] (0.3mm)	6mm	(23mm)	20,000	10	72545	72554
3/4"	.006" (0.2mm)	1/4"	7/8" (23mm)	20,000	10	72546	72555
(19mm)	.012" (0.3mm)	6mm				72548	72557
1"	.006" (0.2mm) 1/4"	1 1/8"	22.222	40	72549	72558	
(25mm)	.012" (0.3mm)	6mm	(28mm)	20,000	10	72551	72560

CRIMPED WIRE END BRUSHES







Diameter	Wire	Shank	Trim	Мах.	Standard	item i	Number
Diameter	Size	Size	Length	RPM	Pack	Steel	Stainless
1/2"	.006" (0.2mm)	1/4"	7/8"	20,000 10	72561	72573	
(12mm)	.012" (0.3mm)	6mm	(23mm)	20,000 10		72563	72575
3/4"	.006" (0.2mm)	1/4"	7/8" 20,000	10	72564	72576	
(19mm)	.012" (0.3mm)	6mm	(23mm)	20,000	10	72566	72578
1"	.006" (0.2mm)	1/4"	1 1/8"		40	72567	72579
(25mm)	.012" (0.3mm)	6mm	(28mm)	20,000	10	72569	72581
1 1/8"	.006" (0.2mm)	1/4"	1 1/8"	20.000	10	72570	72582
(30mm)	.012" (0.3mm)	6mm	(28mm)	20,000	10	72572	72584

STEM-MOUNTED WIRE WHEEL BRUSHES



crimped wire wheels are used on a variety of portable tools and stationary machines. These radial brushes are available in heat-treated Steel, Type 304 Stainless Steel .



Small diameter copper center wheels permanently mounted onto a 1/4" stem to provide a very flexible brushing action



Diameter	Wire	Shank	Face	Max.	Standard	Item Number		
Diameter	Size	Size	Width	RPM	Pack	Steel	Stainless	
2"	.006" (0.2mm)	1/4"	16mm 20,000	10	72585	72591		
(25mm)	.012" (0.30mm)	6mm	TOTTILL		10	72587	72593	
2"	.006" (0.2mm)	1/4"	19mm	20,000	10	72588	72594	
(25mm)	`.012"´ (0.30mm)	6mm	1311111	20,000	10	72590	72596	



Diameter	Wire	Shank	Face	Max.	Standard	item Number		
Diameter	Size	Size	Width	RPM	Pack	Steel	Stainless	
	.008" (0.25mm)					72597	72606	
3" (75mm)	.012" (0.3mm)	1/4" 6mm	16mm	20,000	10	72599	72608	
	.014" (0.35mm)					72600	72609	
	.008 (0.25mm)				10	72602	72611	
3" (75mm)	.012" (0.3mm)	1/4" 6mm	19mm	19mm 20,000		72603	72612	
	.014" (0.35mm)				72605	72614		

P CRIMPED WIRE WHEEL BRUSHES



Diameter	Wire	Shank	Face	Trim	Max.	Standard	Item	Number
Diameter	Size	Size	Width	Length	RPM	Pack	Steel	Stainless
1-1/2"	.006" (0.2mm)	1/4"	1/4"		20,000	10	72615	72630
(40mm)	.012" (0.3mm)	6mm	(6mm)				72617	72632
2" (0.2mm) (50mm) .012" (0.3mm)	1/4"	3/8"		20,000	10	72618	72633	
	.012" (0.3mm)	6mm	(10mm)				72620	72635
2-1/2"	.006" (0.2mm)	1/4"	1/2"		20,000	10	72621	72636
(60mm)	.012" (0.3mm)	6mm	(12mm)				72623	72638
3"	.006" (0.2mm)	1/4"	1/2"		20,000	40	72624	72639
(75mm)	.012" (0.3mm)	6mm	(12mm)			10	72626	72641
4"	.006" (0.2mm)	1/4"	5//8"		20,000	40	72627	72642
(100mm)	.012" (0.3mm)	6mm	(15mm)			10	72629	72644



STEM-MOUNTED WIRE WHEEL BRUSHES



crimped wire wheels are used on a variety of portable tools and stationary machines. These radial brushes are available in heat-treated Steel, Type 304 Stainless Steel and Coarted Brass.

CRIMPED WIRE WHEEL BRUSHES







Diameter	Wire	Shank	Face	Max.	Standard		Item Numbe	r
Diameter	Size	Size	Width	RPM	Pack	Steel	Stainless	Coated Brass
1-1/2"	.006" (0.2mm)	1/4"	1/4"	4,500	10	72645	72659	72669
(40mm)	.012" (0.3mm)	6mm	(6mm)			72647	72660	72670
2"	.006" (0.2mm)	1/4"	3/8"	4,500	10	72648	72661	72671
(50mm)	.012" (0.3mm)	6mm	(10mm)	Ĺ		72650	72662	72672
2-1/2"	.006" (0.2mm)	1/4"	1/2"	4,500		72651	72663	72673
(60mm)	.012" (0.3mm)	.012" 6mm (12mm)		4,000	10	72653	72664	72674
3"	.006" (0.2mm)	1/4"	1/2"	4,500		72654	72665	72675
(75mm)	.012" (0.3mm)	6mm	(12mm)	4,300	10	72656	72666	72676
4"	.006" (0.2mm)	1/4"	5//8"	4,500	10	72657	72667	72677
(100mm)	.012" (0.3mm)	6mm	(15mm)	1,000	10	72658	72668	72678

KNOTTED WIRE WHEEL BRUSHES





Diameter	Wire	Wire Shank No. of Max. Standard Size Size Stocks RPM Pack		Standard	Item Number			
Diameter	Size				Steel	Stainless	Bronze	
3"	.014 (0.35mm)	1/4"		14 12,500	10	72679	72683	72687
(75mm)	.020 (0.5mm)	6mm	14			72680	72684	72688
4"	.014 (0.35mm)	1/4"	10	40.500	10	72681	72685	72689
(100mm)	.020 (0.5mm)	6mm	18	12,500	10	72682	72686	72690

STEM-MOUNTED WIRE CUP BRUSHES



crimped wire wheels are used on a variety of portable tools and stationary machines. These radial brushes are available in heat-treated Steel, Type 304 Stainless Steel and Coarted Brass.

CRIMPED WIRE WHEEL BRUSHES EN1083-2





Diameter	Wire	Shank	Trim Max.		Standard		Item Numb	er
Diamotor	Size	Size	Length	RPM	Pack	Steel	Stainless	Coated Brass
2"	- (0.211111) 4 500		4.500	10	72691	72697	72703	
(50mm)	`.012" (0.3mm)	6mm	(15mm) _{13,000}	13,000		72692	72698	72704
2-1/2"	.006" 1/4"	5/8"		40	72693	72699	72705	
(65mm)	.012" (0.3mm)	6mm	(16mm)	4500, 12,000	10	72694	72700	72706
3"	.006" (0.2mm)	1/4"	3/4"	4,500	10	72695	72701	72707
(75mm)	.012" (0.3mm)	6mm	(20mm)	12,000		72696	72702	72708

CRIMPED WIRE WHEEL BRUSHES







CRIMPED WIRE WHEEL BRUSHES





Diameter	Wire	Shank	Trim	Max.	Standard		Item Numbe	r
Diameter	Size	Size	Length	RPM	Pack	Steel	Stainless	Bronze
2-1/2"	.014" (0.35mm)	1/4"	3/4" (18mm)	12,500	10	72733	72737	72741
(65mm)	.020" (0.5mm)	6mm				72734	72738	72742
3"	.014" (0.35mm)	1/4"	7/8"	12.500	10	72735	72739	72743
(75mm)	.020" (0.5mm)	6mm	(22mm)	.2,000		72736	72740	72744

Кеу:

STEM-MOUNTED NYLON BRUSHES



Stem-mounted Nylon Brushes are used on a variety of portable tools and drills. These radial nylon abrasive wire brushes are available in 80grit 120grit 150grit 180grit and 240 grit, bristle diameter is from 0.7mm - 1.8mm.









Diameter	Wire	Shank	Face	Max.	Standard		Item Numbe	r
Diameter	Size	Size	Width	RPM	Pack	80#	120#	150#
2"	0.7mm	1/4"	8mm	4,500	10	72745	72753	72761
(50mm)	1.2mm	6mm			72746	72754	72762	
2-1/2"	0.7mm	1/4"	10mm	4,500	10	72747	72755	72763
(60mm)	1.2mm	6mm		.,		72748	72756	72764
3"	0.7mm	1/4"		4.500		72749	72757	72765
(75mm)	1.2mm	6mm	12mm	4,500	10	72750	72758	72766
4"	0.7mm	1/4"	14,55	4,500	40	72751	72759	72767
(100mm)	1.2mm	6mm			10	72752	72760	72768

NYLON CUP BRUSHES







Diameter	Wire	Shank	Trim	Max.	Standard		ltem Number	'
Diamotor	Size	Size	Length	RPM	Pack	80#	120#	150#
2"	0.7mm	1/4"	40	4,500	10	72769	72777	72785
(50mm)	1.2mm	6mm	16mm 4,300		72770	72778	72786	
2-1/2"	0.7mm	1/4"	40	4,500	10	72771	72779	72787
(60mm)	1.2mm	6mm	TOTTITI	.,		72772	72780	72788
3"	0.7mm	1/4"		4.500		72773	72781	72789
(75mm)	1.2mm	6mm	23mm	nm 4,500	10	72774	72782	72790
4"	0.7mm	1/4"	22mm	4,500		72775	72783	72791
(100mm)	(100mm) 1.2mm	6mm	22111111	4,300	10	72776	72784	72792

NYLON END BRUSHES





Diameter	Wire	Shank	k Trim	Max.	Standard Pack	item Number			
Diallicici	Size	Size	Length	RPM		Steel	Stainless	Coated Brass	
1"	0.7mm	1/4"	28MM 4,500		72793	72797	72801		
(25mm)	1.2mm	6mm		4,500	10	72794	72798	72802	
1-1/8"	0.7mm	1/4"	OONANA	MM 4,500	10	72795	72799	72803	
(30mm)	1.2mm	6mm	28MM			72796	72800	72804	

NYLON WIRE WHEEL BRUSHES







NYLON Wire Wheel, Narrow Face

Diameter	Wire	Arbor	Face	Trim	Max.	Standard	It	em Numb	er
Diameter	Size	Hole	Width	Length	RPM	Pack	80#	120#	150#
4" (100mm)	0.7mm 1.2mm	M14X2 5/8"-11NC 5/8"(16mm)	1/2*(13mm) 5/8*(16mm)	22mm	4,500	10	72838	72842	72846
4-1/2" (115mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2*(13mm) 5/8*(16mm)	23mm	4,500	10	72839	72843	72847
5" (125mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2*(13mm) 5/8*(16mm)	29mm	4,500	10	72840	72844	72848
6" (150mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2*(13mm) 5/8*(16mm)	33mm	4,500	10	72841	72845	72849

NYLON Wire Wheel, Wide Face

Diameter	Wire	Arbor	Face	Trim	Max.	Standard	li	em Numb	er
Diameter	Size	Hole	Width	Length	RPM	Pack	80#	120#	150#
4" (100mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2*(13mm) 5/8*(16mm)	22mm	4,500	10	72850	72855	72860
5" (125mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2"(13mm) 5/8"(16mm)	29mm	4,500	10	72851	72856	72861
6" (150mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2"(13mm) 5/8"(16mm)	33mm	4,500	10	72852	72857	72862
7" (175mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2"(13mm) 5/8"(16mm)	33mm	4,500	10	72853	72858	72863
8" (200mm)	0.7mm 1.2mm	M14X2 5/8*-11NC 5/8*(16mm)	1/2*(13mm) 5/8*(16mm)	41mm	4,500	6	72854	72859	72864

NYLON WIRE CUP BRUSHES



NYLON Wire CUP BRUSHES

Diameter	Wire	Arbor	Trim	Max.	Standard		Item Numbe	er
Diameter	Size	Hole	Length	RPM	Pack	80#	120#	150#
3" (75mm)	0.7mm 1.2mm	5/8"-11NC M14X 2 M10X1.25 M10X1.5	1" (25mm)	12,500	1	72865	72869	72873
4" (100mm)	0.7mm 1.2mm	5/8" - 11NC M14X 2	1-1/4" (32mm)	8,500	1	72866	72870	72874
5" (125mm)	0.7mm 1.2mm	5/8" - 11NC M14X 2	1-3/8" (35mm)	6,500	1	72867	72871	72875
6" (125mm)	0.7mm 1.2mm	5/8" - 11NC M14X 2	1-3/8" (35mm)	6,000	1	72868	72872	72876

MOUNTED STEM NYLON WHEEL



NYLON Wire Wheel, Narrow Face

Diameter	Wire Arbor		Face Trim		Standard	Item Number			
Diameter	Size	Hole	Width	Length	RPM	Pack	80#	120#	150#
4" (100mm)	0.7mm 1,2mm	M14X2 5/8"-11NC 5/8"(16mm)	1/2"(13mm) 5/8"(16mm)	22mm	4,500	10	72904	72905	72906



NYLON Wire Wheel, Wide Face

Diameter	Wire	Arbor	Face	Trim	Max.	Standard		Item Num	ber
Diameter	Size	Hole Width	Length	RPM	Pack	80#	120#	150 #	
2" (150mm)	0,7mm 1,2mm		25mm		4,500	10	72907	72908	72909



NYLON Wire Wheel, Brush

	Wire	Arbor	Face	Trim	Max.	Standard	li li	tem Numb	er
Diameter	Size	Hole	Width	Length	RPM	Pack	80#	150#	320 #
2" (150mm)	0.7mm 1.2mm		19mm		4,500	10	72910	72915	72919
2" (150mm)	0.7mm 1.2mm		25mm		4,500	10	72912	72916	72920
3" (755mm)	0.7mm 1.2mm		19mm		4,500	10	72913	72917	72921
3" (755mm)	0.7mm 1.2mm		25mm		4,500	10	72914	72918	72922



NYLON Wire Wheel, Brush

IIIameter	Wire	Arbor	Face	Trim	Max.	Standard		tem Numl	ber
	Size	Size Hole Widt	Width	Length	RPM	Pack	80#	120#	150#
2" (150mm)	0.7mm 1.2mm		25mm			10	72923	72924	72925

NYLON Wire Wheel, Brushes



Diameter	Wire	Arbor	Face	Trim	Max.	Standard	lt.	tem Numb	er
	Size	Hole	Width	Length	RPM	Pack	80#	120#	150 #
4" (100mm)	1,2mm					10	72926	72928	72930
5" (150mm)	1.2mm					10	72927	72929	72931

MOUNTED STEM NYLON WHEEL



NYLON Wire Wheel, Narrow Face

Diameter	Wire	Arbor	Face	Trim	Max.	Standard		tem Numl	er
	Size	Hole Width	Width	Length	RPM	Pack	80#	120#	150#
4" (100mm)	0.7mm 1,2mm	M14X2 5/8"-11NC 5/8"(16mm)	1/2"(13mm) 5/8"(16mm)	22mm	4,500	10	72904	72905	72906



NYLON Wire Wheel, Wide Face

Diameter	Wire	Arbor	Face	Trim	Max.	Standard		ltem Num	ber
	Size	Hole	Width	Length	RPM	Pack	Pack 80# 120#		
2" (150mm)	0.7mm 1.2mm		25mm		4,500	10	72907	72908	72909



NYLON Wire Wheel, Brush

	Wire	Arbor	Face	Trim	Max.	Standard	li li	tem Numb	er
Diameter	Size	Hole	Width	Length	RPM	Pack	80#	150#	320 #
2" (150mm)	0.7mm 1.2mm		19mm		4,500	10	72910	72915	72919
2" (150mm)	0.7mm 1.2mm		25mm		4,500	10	72912	72916	72920
3" (755mm)	0.7mm 1.2mm		19mm		4,500	10	72913	72917	72921
3" (755mm)	0.7mm 1.2mm		25mm		4,500	10	72914	72918	72922



NYLON Wire Wheel, Brush

IIIameter	Wire	Arbor	Face	Trim	Max.	Standard		tem Numl	ber
	Size	Size Hole Widt	Width	Length	RPM	Pack	80#	120#	150#
2" (150mm)	0.7mm 1.2mm		25mm			10	72923	72924	72925

NYLON Wire Wheel, Brushes



Diameter	Wire	Arbor	Face	Trim	Max.	Standard	lt.	tem Numb	er
	Size	Hole	Width	Length	RPM	Pack	80#	120 #	150 #
4" (100mm)	1.2mm					10	72926	72928	72930
5" (150mm)	1.2mm					10	72927	72929	72931