



Battery Hold Down with rods kit Installation Instruction

We are striving to build an reliable brand of golf carts parts and accessories.

Hope this manual can assist you to easier install.

For more technical support, please reach us via

Website : www.10101.com

Email : sale_service@10101.com

Facebook : zhong zaiyang

Youtube : 10L0L

Contents

Battery Hold Down.....	1
J Bolt.....	2
Locknut.....	2

Installation Tools

9/16-inch (14mm) Socket.....	1
Battery Lifting Strap.....	1

(See figure 1)

Installation Tools



Installation Steps

1. Park the vehicle on level ground.
2. Turn the key to "OFF" position and remove it from the switch.
3. Make sure the parking brake is set.



4. Remove the seat.

See figure 2



5. Loosen the screws of the battery cables with a 9/16-inch (14mm) socket and remove the battery cables.

See figure 3



6. Loosen the locknuts with a 9/16-inch (14mm) socket, then remove the battery hold down and J bolts kit.

See figure 4



7. Assemble and install the battery hold downs and J bolts kit.

See figure 5



- Put the the battery hold down and J bolts back in place and tighten the locknuts with a 9/16-inch (14mm) socket.

See figure 6



- Install the battery cables and tighten the screws with a 9/16-inch (14mm) socket.

See figure 7



This all completes your installation.