

Gobo Sizes

Please check your projector model in the table below to get the size of the gobo. If you have an unmentioned model, please send it to sevice@logobos.com. Our customer service will check the size of its gobos for you. Instagobo currently only produces glass pattern sheets, please contact us if you need metal pattern sheets.

STANDARD SIZE	Model	Outer diameter	Image Diameter
	A Size	100 mm	58 mm
	B Size	86 mm	60 mm
	D Size	53.3mm	43 mm
	E Size	37.5 mm	28 mm
	G Size	51.8 mm	43 mm
	M Size	66 mm	43 mm
	V Size	22.5 mm	22 mm

ADJ	Model	Outer Diameter	Image Diameter
	AccuScan	25 mm	20 mm
	AccuSpot 250	24 mm	20 mm
	AccuSpot 250 Hybrid	26.7 mm	24.7 mm
	AccuSpot 250II/300	25 mm	20 mm
	Goboprojector LED	26.8 mm	24 mm
	AccuSpot 575	27 mm	22 mm
	AccuRoller	24.5 mm	20 mm
	Icon	26.5 mm	19 mm
	Ikon LED	54 mm	33 mm
	Image 250	53.5 mm	28 mm
	GP 250	32 mm	27 mm
	Encore Profile	66 mm	48 mm
	Quick Scan	21.7 mm	17 mm
	PinPoint Gobo	25.8 mm	19 mm
	Rotogobo	26 mm	19 mm
	Vizi Spot 5R	14 mm	8 mm
	Vizi Spot LED	27 mm	22 mm
	Vizi Spot LED PRO	26.6 mm	23.8 mm
	Whirl	26 mm	20 mm
	X-Color LED	22.5 mm	17 mm

Blizzard	Model	Outer Diameter	Image Diameter
	Kryo Mix	9.9 mm	5.5 mm

Chauvet	Model	Outer Diameter	Image Diameter
	Gobo LED	28.8 mm	24.3 mm
	Gobo LED 2.0	28.6 mm	26 mm
	Gobo Shot IRC	53 mm	40 mm
	EVE 100Z	66 mm	48 mm
	EZgobo	25.7 mm	17 mm
	Intimidator Spot LED 250	24 mm	20 mm
	LFS-5	25.4 mm	19 mm
	LED-75DMX	40 mm	18 mm
	LED Followspot 75ST	25.4 mm	19 mm
	Follow Spot 75ST	25.4 mm	19 mm
	Q-Spot 150 LED	25.7 mm	18 mm
	Q-Spot 250	37.2 mm	31 mm
	Q-Spot 260 LED	25.9 mm	19 mm
	Q-Spot 575	31 mm	22.5 mm
	R2 Spot	27 mm	23.8 mm
	SX Gobo	51 mm	40.5 mm
	DMX 690	23.7 mm	17.5 mm
	EZGobo LED	25.8mm	18.6mm (metal only)
	Followspot 400G TFX-FS360	35.8 mm	27.8 mm
	Gobo Zoom LED	28.8 mm	24.3 mm
	Gobo Zoom LED 2.0	28.6 mm	26 mm
	Gobo Zoom USB	25.74mm	19.38mm
	ILS 515DMR	26.8 mm	21 mm
	ILS 515M	27 mm	19 mm
	ILS 606DBR	27 mm	19 mm
	ILS 606DSR	27 mm	19 mm
	ILS 625DCR	27 mm	19 mm
	Intimidator Barrel LED 300	23.8 mm	20.9 mm

Intimidator Scan LED 300	23.8 mm	20.9 mm
Intimidator Spot 2.0 HTI	23.5 mm	17.5 mm
Intimidator Spot 250	26.7 mm	24.5 mm
Intimidator Spot LED 350/355	24 mm	20 mm
Intimidator Spot XYZ	23.8 mm	20 mm
Legend 1200E Spot	37.3 mm	30 mm
Legend 150 R	26.5 mm	21 mm
Legend 2000	31 mm	20 mm
Legend 250 RX	26.5 mm	19 mm
Legend 3000	31 mm	24 mm
Legend 3000X	29 mm	24 mm
Legend 300E Spot	26.8 mm	23.9 mm
Legend 5000	29 mm	24 mm
Legend 5000X	29 mm	24 mm
Legend 550	26.7 mm	22 mm
LFS-5(d)	25.4 mm	19 mm
LFS-75 DMX	40 mm	18 mm
Q-Scan 150	27.7 mm	21.5 mm
Q-Scan 250	27.7 mm	21.5 mm
Q-Spot	27 mm	19 mm
Q-Spot 150	27 mm	19 mm
Q-Spot 152	25 mm	21 mm
Q-Spot 160 LED	25.8 mm	18.2 mm
Q-Spot 200	25.6 mm	20.5 mm
Q-Spot 300	37 mm	28 mm
Q-Spot 560 LED	32.5 mm	27 mm
Trackscan 250 R	26.8 mm	18 mm

Clay Paky	Model	Outer Diameter	Image Diameter
	Alpha Spot 575	37.5 mm	23 mm
	Alpha Spot 300	25.7 mm	23 mm
	Alpha Spot 1200	37.5 mm	25 mm
	Mythos	25.9 mm	13 mm
	Supersharpy	25.9 mm	16 mm
	Scenius - Specify Rot1 or Rot2	32.8 mm or 31.5 mm	
	VIP Changer	31.5 mm	23 mm
	VIP 150/250/300	51.8 mm	33 mm (Metal Bezel)
	VIP 1200	51.8 mm	45 mm
	Alpha Profile 1200	37.5 mm	25 mm
	Alpha Spot 700	37.5 mm	25 mm
	Alpha Spot Easy 1200	37.5 mm	25 mm
	Alpha Spot HPE 1200	37.5 mm	25 mm
	Alpha Spot HPE 300	25.7 mm	23 mm
	Alpha Spot HPE 575	37.5 mm	25 mm
	Golden Scan	66 mm	43 mm
	Golden Scan HPE	51.8 mm	36 mm
	Golden Spot 1200	51.8 mm	36 mm
	MiniScan HP3	25.8 mm	19 mm
	S.I.P. 300	31.5 mm	24 mm
	Stage Profile Plus	51.8 mm	48.7 mm
	Stage Scan	51.8 mm	36 mm
	Stage Zoom 1200	51.8 mm	36 mm
	Super Scan	66 mm	57 mm
	Super Scan Zoom	51.8 mm	36 mm
	Tiger Scan	51.8 mm	36 mm
	V.I.P. 250 ALO	31.5 mm	24 mm
	V.I.P. 250 ALO/ST	31.5 mm	24 mm
	V.I.P. 300 DIA	51.8 mm	33 mm

Coemar	Model	Outer Diameter	Image Diameter
	I Spot 150/575	32.9 mm	26 mm
	I Spot 1200	32.8 mm	28 mm
	I Profile Flex	32.8 mm	28 mm
	I Spot Flex	32.8 mm	28 mm
	CF 7 HE	25.8 mm	19.5 mm
	Infinity Spot S	27 mm	21 mm
	Infinity Spot XL	32.8 mm	25 mm
	NAT MM 1200 Zoom BBI	50 mm	37.5 mm
	NAT MM 2500 Zoom	50 mm	37.5 mm
	NAT MM 4000 Zoom	50 mm	37.5 mm
	ProSpot 150	32.9 mm	26 mm

ProSpot 250 LX	25.8 mm	19 mm
ProSpot 575	32.9 mm	26 mm

Derksen	Model	Outer Diameter	Image Diameter
	GL L60 LED	70 mm	32 mm
	GL 100/150/200	70 mm	36 mm
	GL 575/700/1200	105 mm	60 mm
	GL 575/700/1200	105 mm	68 mm
	Gobo Top	37 mm	20 mm
	PHOS 20 LED	50 mm	32 mm
	PHOS mini LED	37.5 mm	15 mm

ECO	Model	Outer Diameter	Image Diameter
	Spot 10/C25/C40/C60 (Ultra Wide Lens)	37.5 mm	23 mm
	Spot C20/C25/C40/C60	37.5 mm	25 mm (E Size)
	Spot B90/B150/B300	66 mm	48 mm (M Size)
	Spot 90-SO/90E-SO/90PCE-SO	66 mm	22 mm
	Spot A10/A25/B40/B60/25D/40D	53.3 mm	25 mm
	Spot LED 10/25/30/40E/40C/80CE	37.5 mm	25 mm (E Size)
	Spot 16/35/70	37.5 mm	25 mm
	Spot LED 80/100/150/250	66 mm	48 mm (M Size)
	Spot 2500 HID	86 mm	60/64 mm (B Size)

Elation	Model	Outer Diameter	Image Diameter
	E Spot LED	26.9 mm	24 mm
	E Spot LED II	27 mm	22 mm
	E Spot LED III	26.8 mm	21.4 mm
	Focus Spot 250/575	26.9 mm	23 mm
	Design Spot 250/575	26.7 mm	23 mm
	Image Pro 300 Changer	31.5 mm	23 mm
	Image Pro 300	51.8 mm	33 mm
	Image Pro 300	51.8 mm	33 mm (Metal Bezel)
	Power Spot 250/575	26.9 mm	23 mm
	Platinum Spot LED Pro	26.7 mm	22 mm
	Active Scan 250	26.9 mm	23 mm
	Active Wave 250	26.9 mm	23 mm
	Color Spot 575	27 mm	23 mm
	Design Spot 1400	37.5 mm	31 mm
	Design Spot 250WH	27 mm	23 mm
	Design Spot 300 Pro	26.9 mm	23 mm
	Design Spot LED	26.9 mm	24 mm
	ELAR Image X	37.5 mm	20 mm
	ELAR Image XR	37.5 mm	20 mm
	Image IP2	51.8 mm	35.5 mm
	Joy-150	26 mm	22 mm
	Joy-300	26 mm	22 mm
	Patend 1200	37.5 mm	27 mm
	Platinum Spot 5R	14 mm	7 mm
	Power Spot 575IE	26.9 mm	23 mm
	Power Spot 700	26.9 mm	23 mm
	Power Spot 700 CMY II	26.9 mm	23 mm
	Vision Scan 250	27 mm	23 mm
	Vision Scan 575	22.5 mm	18 mm

ETC / Source Four	Model	Outer Diameter	Image Diameter
	Source Four	86 mm	64/60 mm (B Size)
	Source Four Jr	66 mm	48 mm (M Size)
	Source Four Mini LED	37.5 mm	23 mm (glass in bezel)
	Source Four Mini	37.5 mm	25.4 mm (E Size, glass in bezel)
	Revolution	66 mm	59 mm

GOLUX 1000/600	Model	Outer Diameter	Image Diameter
	Rotator	37.5 mm	30 mm
	Gobo Changer Tabbed Wheel	43.3 mm	30 mm

Gantom	Model	Outer Diameter	Image Diameter
	iQ	19 mm	10 mm

Griven	Model	Outer Diameter	Image Diameter
	Goboclip	53.3 mm	40 mm (D Size)

High End System	Model	Outer Diameter	Image Diameter
	Cyber light	44.4 mm	37 mm
	Studio Spot 250	25 mm	22 mm
	Studio Spot 575	36.3 mm	31 mm
	Cyberlight Turbo	44 mm	38 mm
	Image Marketing Projector	37.5 mm	35 mm
	Intellabeam	25 mm	22 mm
	Intellabeam 700 HX	25 mm	22 mm
	SHOWGUN	64.9 mm	53 mm
	Technobeam	25 mm	22 mm
	Technobeam FX Wheel	36 mm	26 mm
	Trackspot	25 mm	22 mm
	X-Spot	36.4 mm	31.75 mm

Ikea	Model	Outer Diameter	Image Diameter
	Isbrytare	50 mm	32 mm

Litegraphic	Model	Outer Diameter	Image Diameter
	All Models	50 mm	38 mm
	until 12/2010	51.8 mm	40 mm

Martin	Model	Outer Diameter	Image Diameter
	Mabia PR1	53.3 mm	38 mm (D Size)
	MAC 250	22.5 mm	17 mm
	MAC 250 Entour	22.5 mm	17 mm
	MAC 250 Krypton	22.5 mm	17 mm
	MAC 500/550/575/700/918	27.9 mm	23 mm
	MAC 2000/III Performance	37.5 mm	30 mm
	MiniMAC Maestro	37.5 mm	30 mm
	MiniMAC Profile	22.5 mm	17 mm
	MX-10	22.5 mm	17 mm
	SmartMAC	27.8 mm	23 mm
	SCX 600/700/800	22.5 mm	17 mm
	Quantum Profile	27.9 mm	24 mm
	CX-10	22.5 mm	17 mm
	EGO 1-3	22.5 mm	16 mm
	Exterior 1200 Image Projector	53.3 mm	48 mm
	Imagescan	53.3 mm	44 mm
	Mac 350 Entour	27.9 mm	23 mm
	Mania DC3	54 mm	38 mm
	Mania EF3	54 mm	43 mm
	RoboScan Pro 518	21.5 mm	14 mm
	RoboScan Pro 918	27.9 mm	23 mm

Osram Kreios G1 LED	Model	Outer Diameter	Image Diameter
		37.5 mm	28 mm

Raztech 300	Model	Outer Diameter	Image Diameter
		50 mm	27 mm

Robe	Model	Outer Diameter	Image Diameter
	ColorSpot 170/250/575/700	26.8 mm	22 mm
	ColorSpot 1200AT	37.5 mm	33 mm
	ColorSpot 2500 EAT	37.5 mm	31.5 mm
	Spot 150/160/170/250/575	26.8 mm	22 mm
	ClubSpot 250	26.8 mm	19 mm
	ColorSpot 1200	37.5 mm	29 mm
	ColorSpot 700E AT	26.8 mm	22 mm
	Image Spot 250	37.5 mm	29 mm
	MS Zoom 250	37.5 mm	19 mm
	Scan 250	26.8 mm	19 mm
	Scan 575	26.8 mm	19 mm

Robert Juliat	Model	Outer Diameter	Image Diameter
	TIBO	66 mm	48 mm (M Size)
	ZEP	66 mm	48 mm (M Size)

Stage Ape	Model	Outer Diameter	Image Diameter
	Ape Gobo Spot	48 mm	38 mm

Tech Loghting	Model	Outer Diameter	Image Diameter
---------------	-------	----------------	----------------

T156

54 mm

27 mm

Times Square	Model	Outer Diameter	Image Diameter
	Gobo 70/150	66 mm	48 mm (Metal Bezel)
	MR75	36 mm	25 mm (Metal Bezel)

Varilite	Model	Outer Diameter	Image Diameter
	VL 1000	Metal only	Metal only
	VL 2000/2500	22.5 mm	16.5 mm
	VL 3000	37.5 mm	26.5 mm (mounted in rot.ring)
	VL 3500	37.5 mm	26.5 mm (mounted in rot.ring)
	VL 4000	37.5 mm	29.5 mm (mounted in rot.carrier)